

Epson TM-T88V Thermal Receipt Printer

A compact thermal printer with the ultimate in user-friendliness. Small and compact, this fast thermal printer delivers print at speeds up to 300mm/sec. The TM-T88V employs a drop-in roll paper loading system that makes paper replacement fast and easy. It also features thoughtful design elements that make head cleaning and other maintenance tasks a breeze. Industry-first true grayscale printing of graphics.

Product features

- Modular, user-friendly design
- Fast and smooth
- Drop in paper loading
- Autocutter
- Easy to read LEDs
- High speed printing up to 300mm/second
- Easy maintenance and high reliability
- Page mode printing
- Flash ROM for logo storage
- Increased flexibility with a standard built-in USB in addition to having a UIB interface
- Ideal for higher volume operations
- Ability to bar code receipt to simplify returns
- 4 year warranty



Standard inclusions

- TM-T88V Thermal printer
- Easy to install and configure manual
- Parallel, serial or USB interface cables
- Unlimited help desk support assistance

Ordering details

Epson TM-T88V thermal receipt printer **80503USB**

Last updated: January 2012

CEI Pty Limited trading as Raeco®

75 Rushdale Street, Knoxfield, Victoria 3180 AUSTRALIA

Phone: 1300 727 231 **Fax:** 1300 727 241

E-mail: support@raeco.com.au **Web:** www.raeco.com.au



Epson TM-T88V Thermal Receipt Printer

Specifications

Print Method	Thermal line printing
Print Font	9 x 17 / 12 x 24
Column Capacity	56 / 42 columns
Character Size	0.99 W x 2.4 H mm / 1.41 W x 3.39 H mm
Character Set	95 alphanumeric, 16 set international, 128 x 43 graphic Traditional / Simplified Chinese, Thai, Japanese, Korean Barcode: UPC-A, UPC-E, Jan 8 (EAN), Jan 13 (EAN), Code 39, Code 93, Code 128, ITF, Codabar, GS1-128, GS1 DataBar
Characters per inch	20.0 cpi / 15.0 cpi
Interface	RS-232, Bi-directional parallel, USB, USB Plus Power, Ethernet (10/100 Base-T), Wireless LAN (IEEE802.11b)
Data Buffer	4 KB or 45 bytes
Print Speed	300 mm / sec
Paper Dimensions	Roll paper: 79.5 \pm 0.5 W x dia (max) 83.0 mm
Paper Thickness	0.06 to 0.07 mm
Power	24 VDC \pm 7%
Power Consumption	Approx. 1.8A (mean)
D.K.D. Function	2 drivers
Reliability	20 million lines
Overall Dimensions	145 W x 195 D x 148 H mm
Mass	Approx 1.6 kg
EMC Standards	FCC, VCCI, CE marking, AS/NZS CISPR22 class A. GOST-R
Safety Standards	UL, CSA, EN, TUV, GOST-R

Last updated: January 2012

CEI Pty Limited trading as Raeco®

75 Rusdale Street, Knoxfield, Victoria 3180 AUSTRALIA

Phone: 1300 727 231 **Fax:** 1300 727 241

E-mail: support@raeco.com.au **Web:** www.raeco.com.au

